

BALDEN

*Technical Datasheet
for
FFC(T)25 Free Fall Lifeboat*



BALDEN BOAT
Evliya Çelebi Mah. Genç Osman Cad
No.44A/1 Tuzla - İstanbul / Türkiye
balden@baldenboat.com.tr
www.baldenmarine.com

Regulation and Certification

- ◆ Applicable rules and regulations In accordance with IMO/SOLAS requirements, LSA code and European Council Directive 2014 / 90 EU on Marine Equipment (MED)
- ◆ Certificate MED

Boat Particulars

- ◆ Type FFC25 (FFT25 for tanker type)
- ◆ Max. Capacity 25 persons
- ◆ Overall L x B x H 6.23 x 2.68 x 3.00 m
- ◆ Material Fire retardant glass reinforced polyester (GRP)
- ◆ Weight (fully equipped) 3400 kg (3650 kg for tanker type)
- ◆ Davit Load (with 25 persons x 82,5 kg) 5462 kg (5712 kg for tanker type)
- ◆ Launching ramp angle 30°
- ◆ Launching ramp length 7 m
- ◆ Max. installation height 18 m
- ◆ Buoyancy material Polyurethane foam
- ◆ Sprinkler system (for tanker type) Stainless steel piping system.

Propulsion and Performance

- ◆ Engine Nanni Diesel N4.38
- ◆ Engine power 27.6 kW – 37.5 HP
- ◆ Propeller material Brass
- ◆ Speed Min. 6 knots in calm water
- ◆ Cooling Closed cooling with heat exchanger
- ◆ Fuel tank 120 Lt. Stainless steel.

Packing and Securing

- ◆ Packing Delivering with canvas
- ◆ Securing Delivering in transport cradle

Possible Davit Solutions

- ◆ DENİZSAN DSFFD60
- ◆ Others On request