BALDEN

Technical Datasheet for

FFC(T)25 Free Fall Lifeboat



BALDEN MARINE
A: Yunus Mah. Atölyeler Sok.
No: 14 Kartal - İstanbul
T: +90 216 447 23 16
E: sales@baldenmarine.com
baldenmarine.com

Regulation and Certification

Applicable rules and regulations In accordance with IMO/SOLAS requirements,

> LSA code and European Council Directive 2014 / 90 EU on Marine Equipment (MED)

♦ Certificate

MED

Boat Particulars

◆ Type FFC25 (FFT25 for tanker type)

♦ Max. Capacity 25 persons

♦ Overall L x B x H 6.23 x 2.68 x 3.00 m

♦ Material Fire retardant glass reinforced polyester (GRP)

Weight (fully equipped) 3400 kg (3650 kg for tanker type)

♦ Davit Load (with 25 persons x 82,5 kg) 5462 kg (5712 kg for tanker type) 30° Launching ramp angle

♦ Launching ramp length 7 m 18 m ♦ Max. installation height

Polyurethane foam Buoyancy material

♦ Sprinkler system (for tanker type) Stainless steel piping system.

Propulsion and Performance

Nanni Diesel N4.38 ♦ Engine 27.6 kW - 37.5 HP

♦ Engine power Propeller material Brass

Min. 6 knots in calm water ♦ Speed

Closed cooling with heat exchanger ♦ Cooling

♦ Fuel tank 120 Lt. Stainless steel.

Packing and Securing

Delivering with canvas Packing

Delivering in transport cradle ♦ Securing

Possible Davit Solutions

◆ DENİZSAN DSFFD60

♦ Others On request